

MATERIAL DATA SAFETY SHEET

Tiger Foam® IGNITION BARRIER

ISSUE DATE: SEPTEMBER 2011 Form # TFMSDS-100 Last revision: September 1, 2011 2011

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Brand: Tiger Foam® Ignition Barrier

Chemical Product: Intumescent Latex Coating

Chemical Floudet. Intumescent Latex Coating

Manufacturer:

COMMERCIAL THERMAL SOLUTIONS, INC.

6 Worthington Avenue

Spring Lake, New Jersey 07762

Emergency Overview and Contacts

Product Information: 1-800-664-0063

International Phone: (001) 1+732.927.2090

IN CASE OF EMERGENCY CALL:

Transportation Emergency:

CHEMTREC (Domestic): 1-800-424-9300 CHEMTREC (Int'I): (703)527-38873

2. HAZARDS IDENTIFICATION

Emergency Overview

WARNING! EYE, SKIN, LUNG IRRITANT. May cause eye irritation. May cause skin irritation. Repeated exposure may cause allergic skin reaction. Skin sensitizer. Possible stomach irritation and nausea if swallowed.

Potential Health Effects

Use in a well ventilated area and with certified respiratory protection to avoid irritation.

Effects of Overexposure

Entry Route:

Inhalation:Short term exposure may cause irritation of nose, throat, and lungs.Eyes:Causes irritation. Repeated exposure may cause allergic dermatitis.

Skin: Causes irritation. Repeated exposure may cause allergic dermatitis.

Ingestion: Possible stomach irritation and nausea. No other harmful effects anticipated.

If accidental contact occurs, follow the appropriate first aid procedure described in Section 4 of this MSDS.

3. COMPOSITION

Chemical Name (common names)CAS NumberPercentageTriamini-s-trianzine108-78-010 - 10%Other MaterialsNot Regulated60 - 100%

(NOTE: See Section 8 of this MSDS for Exposure Guidelines)

(NOTE: See Section 11 of this MSDS for Toxicological Information- LC₅₀ and LD₅₀)

4. FIRST AID

Inhalation: If breathing difficulty is experienced, move to area free of exposure. Provide fresh air. If necessary, provide oxygen

or artificial respiration by trained personnel and obtain medical attention.

Eye Contact: Flush with clean water for at least 15 minutes and obtain medical attention.

^{*}Tiger Foam® Ignition Barrier is registered by the manufacturer, COMMERCIAL THERMAL SOLUTIONS, INC.

TIGER FOAM® IGNITION BARRIER ISSUE DATE: SEPTEMBER 2011 LAST REV: September 1, 2011

Skin Contact: Use a rag to remove liquid from skin and remove contaminated clothing. Contact may cause mild irritation or

temporary darkening of skin. Persistent washing with soap and water will eventually remove all residues. If

irritation persists, obtain medical attention.

Ingestion: Drink 1 to 3 glasses of water and seek immediate medical attention. Do not induce vomiting. Never give anything

orally to an unconscious person.

5. FIRE FIGHTING MEASURES

Extinguishing Media: Dry Chemical, carbon dioxide, or alcohol foam.

Firefighting Procedures: Wear self-contained breathing apparatus. Wear all turn out gear (boots, trousers, helmet, gloves, and hood).

Unusual Fire/Explosion Hazards: Dried solid residue is slightly combustible.

6. ACCIDENTAL RELEASE MEASURES / DISPOSAL CONSIDERATIONS

Personal Precautions: Evacuate all unnecessary personnel; contain the area if possible. Wear skin, eye, and respiratory protection and equipment. Ventilate the area.

Environmental Precautions: Containment should include preventing the spill from entering drains, sewers, waterways, groundwater, or soil.

Clean Up Procedures/Neutralization: Use Soap and Water to clean-up. Material may need to be placed in a container prior to disposal. Contact local waste disposal for guidance.

7. HANDLING AND STORAGE INFORMATION

Handling: Use only in a well ventilated area with certified respiratory protection or with a power air purifying respirator (PAPR). Wear protective glasses or goggles, neoprene gloves, and clothing that protects from dermal exposure.

Storage: Store at or between 40°F to 90°F (5°C to 32°C) and keep out of direct sunlight. DO **NOT** allow product to freeze. KEEP OUT OF REACH OF CHILDREN.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Read all product instructions before using.

Personal Protective Equipment

Respiratory Protection: Use products only in a well ventilated area. If applying the product with an airless sprayer, a NIOSH approved air purifying respirator equipped with an organic vapor cartridge and a particulate filter. If applying in a confined space or in an area with little or no ventilation use a powered air purifying respirator (PAPR). The type of respiratory protection selected must comply with the requirements set forth in OSHA's Respiratory Protection Standard (29 CFR 1910.134).

Hand Protection: Use chemically resistant gloves (i.e. Nitrile gloves). Nitrile/butadiene rubber, Butyl Rubber, polyethylene, PVC (vinyl), or neoprene gloves are also effective. Glove selection should take into account potential body reactions to certain materials and manufacturer's instructions for use.

Eye Protection: Use safety glasses or goggles. An eye wash station or portable eye wash bottle should be in the area.

Skin Protection: Avoid contact with skin. Use clothing that protects against dermal exposure.

General Hygiene: Do not eat, drink, or smoke while handling this product. Always use in well ventilated area. Wash after handling. Do not breathe vapors. Avoid contact with skin and hands.

Exposure Guidelines

Triamini-s-trianzine OSHA Not Available

(None of the components in this product are listed by IARC, NTP, OSHA or ACGIH as a carcinogen).

TIGER FOAM® IGNITION BARRIER

ISSUE DATE: SEPTEMBER 2011 LAST REV: September 1, 2011

9. PHYSICAL AND CHEMCIAL PROPERTIES

Appearance:	Opaque Liquid
Odor:	Low VOC paint-like odor
pH:	7-8
Melting/Freezing Point:	32° F
Boiling Point:	212° F
Flash Point:	Not Available
Specific Gravity:	1.25
Solubility:	Not Available
Partition Coefficient N-octanol/water:	Not Available
Auto-ignition Temperature:	Not Available
Decomposition Temperature:	Not Available
Odor Threshold:	Not Available
Evaporation Rate:	Not Available
Flammability:	Not Available
Flammability Limits:	Not Available
Vapor Pressure:	Not Available
Vapor Density:	Not Available

10. STABILITY AND REACTIVITY

Stability: This product is considered stable under normal and anticipated storage and handling conditions.

Materials to Avoid: Strong oxidizers.

11. TOXICOLOGICAL INFORMATION

Acute Toxicity:

Inhalation: Not Available Ingestion: Not Available Skin: Not Available

12. ECOLOGICAL INFORMATION

Not Available

13. DISPOSAL CONSIDERATIONS

DISPOSE OF EMPTY PAILS ACCORDING TO APPLICABLE FEDERAL, STATE, PROVINCIAL AND LOCAL REGULATIONS. CHECK WITH YOUR LOCAL WASTE DISPOSAL SERVICE FOR GUIDANCE.

Pails and lids are recyclable HDPE 2 plastic. Check with your local waste disposal service for recycling guidance.

14. TRANSPORTATION

Shipping Information

Containers Greater Than 1000 cu. cm. (1 liter)

Ground NON-REGULATED GOODS Air NON-REGULATED GOODS

DOT IATA

Water NON-REGULATED GOODS

IMDG

15 REGULATORY

OSHA Hazcom Standard Rating:

Non Hazardous Material

ISSUE DATE: SEPTEMBER 2011 LAST REV: September 1, 2011

16. OTHER

NFPA: Health Hazard 1; Flammability 1; Reactivity 0 HMIS III: Health 1; Flammability 1; Physical Hazard 0

The information and recommendations set forth herein are presented in good faith and believed to be correct as of the date hereof. The manufacturer makes no representations as to the completeness or accuracy thereof. Information is supplied upon the condition that the persons receiving it will make their own determination as to its suitability for their purposes prior to use. In no event will the manufacturer be responsible for damages of any nature whatsoever resulting from the use of or reliance upon information. No representations or warranties, either expressed or implied, of merchantability or fitness for a particular use are made hereunder with respect to this information or the product to which information refers.

Information contained herein is deemed to be reliable, conservative and accurate. Commercial Thermal Solutions, Inc. reserves the right to change the design, specifications or any other features at any time and without notice, while otherwise maintaining regulatory compliance.

LAST REVISION: September 2011 TFMSDS-100
BASED ON INFORMATION SUPPLIED BY MANUFACTURER